



Плитка / мешалка SLR



SI Analytics

По вопросам продаж и поддержки обращайтесь:

Архангельск (8182)63-90-72
Астана +7(7172)727-132
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Казань (843)206-01-48

Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81
Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41

Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78

Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

сайт: <http://sianalytics.nt-rt.ru> || эл. почта: ssc@nt-rt.ru

SLR

In addition to fast or temperature controlled heating, a lot of applications also require liquids to be stirred. Using our laboratory stirrer SLR with heating, the process of mixing liquids can be selected from careful to intense, and the device can also be used for speedy heating up or controlled temperature adaptation.

Technical data

Heating function	
heating power (kW)	0.9
heated zone (mm)	Ø 155
max. hot plates temperature (°C)	approx. 550
min. time to boiling point 1 l H ₂ O* (min)	approx. 15
temperature sensor connector	yes, Pt 1000
setting accuracy with temperature sensor (°C)	1
controlling accuracy with temperature sensor** (°C)	± 2 ... 5
hot plate material	glass ceramic
hot plates area (mm)	235 x 235
digital set/actual temperature display (temperature sensor connector)	yes
Stirring function	
max. rpm (min ⁻¹)	100 - 1100
setting accuracy rpm (min ⁻¹)	10
max. stirring volume (l H ₂ O)	10
digital set/actual rpm display	yes
General data	
dimensions (L x W x H in mm)	370 x 240 x 85
weight (kg)	approx. 3.8
max. load (kg)	25
admissible ambient temperature (°C)	10 - 40
admissible air humidity (%)	85
protection type	IP 20
protection class	1
housing material	die-cast
cable connector	fixed cable
mains connection (V/Hz)	230 V, 50/60 or 115 V, 50/60
Order No. 230 V	28 541 6373
Order No. 115 V***	28 541 6279

Ordering information

Description	Type No.	Order No.
Temperature sensor stainless steel shaft (V4A), Pt 1000 sensor, 1 m fixed cable with 2 x 4 mm banana plug, length 170 mm, Ø 4 mm, -30 ... + 200 °C	W5791NNHT	28 510 5308
Temperature sensor glass shaft, Sensor Pt 1000, 1 m fixed cable with 2 x 4 mm banana plug, length 250 mm, Ø 6 mm, -30 ... + 200 °C	W5780NNHT	28 510 5238
Stand rod with fixing nut (M8) stainless steel, Ø 10 mm, length 450 mm	Z 601	28 541 6492
Temperature sensor holder clamp with extension rod made of stainless steel, connector	Z 602	28 541 6505
Magnetic stirrer rod set for standard applications / AlNiCo5, circular cross-section, PTFE coated, 1 piece 15, 20, 30, 40, 50, 60, 70, 80 mm each	Z 603	28 541 6554
Magnetic stirrer ripe for medium volumes SmCo, circular cross-section, PTFE coated, 5 pieces 9 x 15 mm each	Z 604	28 541 6562
Magnetic stirrer for large volumes SmCo, elliptic cross-section, PTFE coated, 1 piece 19 x 75 mm each	Z 605	28 541 6579
Compressed-air connector (only SLK) for use in an aggressive environment (subsequent installation only by manufacturer)	Z 607	28 541 6595
Compressed-air connector set (only SLK)	Z 608	28 541 6608

* measured in 3 l glass beaker at 25 °C ambient temperature and 1 bar air pressure

** depending on liquid quantity, heat capacity, and ambient temperature

*** the above measurement values may deviate slightly when using the 115 V version

• CE sign
Council Directive 89/336/EMC
(electromagnetic compatibility)
Council Directive 73/23/EMC (low-voltage directive), last modified by the Council Directive 93/68/EMC

По вопросам продаж и поддержки обращайтесь:

Архангельск (8182)63-90-72
Астана +7(7172)727-132
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Казань (843)206-01-48

Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81
Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41

Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78

Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93